

HOOTER CUM SPEAKER

(MS Body)

Product Overview

Exclusive range of Fire Alarm Hooter (Sounder) Conventional type with made out of 16/18 SWG CRCA Sheet duly powder coated with PO Red Colour. The wall mounted medium frequency hooter designed as per NFPA-72 to complete the demand of Fire Alarm systems in several areas of residential, commercial & Industrial application. The Fire Alarm Hooter is a device that produce sound when Manual Call Point & Detector sense any kind of fire activity. It has dual tone sound and it is enough to make alert everyone inside the building.



AGNI-404

FEATURES:-

Compatibility with Fire Alarm/other safety Control Panel

Continually rated

MS Enclosure

TECHNICAL SPECIFICATION OF HOOTER CUM SPEAKER

Make	Agni Instruments Engineers (I) Pvt. Ltd.
Model	AGNI-404
Construction Material	16 SWG MS CRCA Sheet, Powder Coated
Colour	PO Red
Dimensions	L-138 x D-70/50 x H-187
Cable Entry	Top
Mounting Holes	2 Nos. (4mm)
Knock Out	19mm
Output	80db @ 25 MTR
Speaker	AGNI8 OHM
Operating Voltage	100/70 VOLT AC RMS
Alarm Current	5Watt
LMT with Adjustable Sound Output	2.5 Watt, 5 Watt

